




High Performance Product Catalog

ITECH - YOUR POWER TESTING SOLUTION





Communication interface



IT-E177

RS232 communication interface and analog interface


Applicable model: IT7800, IT7900



IT-E178

GPIB communication interface

Applicable model: IT7800, IT7900



IT-E168 / IT-E169

Fiber optical kit for single unit or cabinet parallel connection

Applicable model: IT6000 series, IT7800, IT7900



IT-E121 RS232 Communication interface, with RS232 standard communication cable

Applicable model: IT6100, IT6800, IT6322, IT6302, IT8500+, IT8500



IT-E122 USB Communication interface, with USB standard communication cable

Applicable model: IT6100, IT6800, IT6322, IT6302, IT8500+, IT8500



IT-E123 RS485 Communication interface, with RS485 interface

Applicable model: IT8500+, IT8500, IT6800, IT6100, IT6322



IT-E1205 GPIB interface

Applicable model: IT-M series



IT-E1206 USB/LAN interface

Applicable model: IT-M series



IT-E1207 RS232/CAN interface

Applicable model: IT-M series



IT-E1208 External analog/RS485 interface

Applicable model: IT-M series



IT-E1209 USB interface

Applicable model: IT-M series



IT-E166 GPIB interface

Applicable model: IT8000, IT6000B, IT6000C, IT6000D



IT-E167 External analog/RS232 interface

Applicable model: IT8000, IT6000B, IT6000C, IT6000D

Optional keyboard



IT-253 Keyboard
Help IT8500 series electronic load to complete Auto-test function
Applicable model: IT8500 series



IT-254 Keyboard
Coordinating IT8500+ series electronic load to realize automatic testing function
Applicable model: IT8500+ series

Quick Charger Controller




IT-E255A
Applicable model: IT8500+ series

IT-E255M
Applicable model: IT8500+, IT8800, IT8700


Test leads

IT-E30110-AB	10A / 1m / Alligator clips - Banana plugs	A pair of red and black test line
IT-E30110-BB	10A / 1m / Banana plugs - Banana plugs	A pair of red and black test line
IT-E30110-BY	10A / 1m / Banana plugs - Y-type terminals	A pair of red and black test line
IT-E30312-YY	30A / 1.2m / Y-type terminals	A pair of red and black test line
IT-E30320-YY	30A / 2m / Y-type terminals	A pair of red and black test line
IT-E30615-OO	60A / 1.5m / Ring terminals	A pair of red and black test line
IT-E31220-OO	120A / 2m / Ring terminals	A pair of red and black test line
IT-E32410-OO	240A / 1m / Ring terminals	A pair of red and black test line
IT-E32420-OO	240A / 2m / Ring terminals	A pair of red and black test line
IT-E33620-OO	360A / 2m / Ring terminals	A pair of red and black test line



IT-E151A 19 Rack mount kit
Applicable model: IT8900 / IT8500 <1800W series, IT8811, IT8812, IT6800, IT6900, IT6322, IT6120, IT6150, IT6400, IT6700H (except IT6726)

Rack mount kit



IT-E154A/IT-E154B Rack mount kit
Applicable model: IT-M series



IT-E152 Rack mount kit
Applicable model: IT8200/ IT6700 series



IT-E601 300V
IT-E601H 1000V

Pin type lead
Rubber straight plug – Probe crown round head

Applicable model:IT5100



IT-E602 300V
IT-E602H 1000V

Large clip type lead
Rubber straight plug – Alligator clips

Applicable model:IT5100



IT-E603 300V
IT-E603H 1000V

Pin type lead
Rubber straight plug – Probe double pin plugs


Applicable model:IT5100



IT-E604 300V
IT-E604H 1000V

Black straight plug - Universal pen + Alligator clip

Applicable model:IT5100




IT-E605

Zero adjustment board (suitable for different probe)

Applicable model:IT5100

Current sensor



IT - E185 (option)

Measuring fixture box (250 V / 15 A), easy wiring test

Applicable model:IT9100



IT-E190-25A (option)

Current sensor

Applicable model:IT9100, ITS9500



IT-E190-50A (option)


Current sensor

Applicable model:IT9100, ITS9500

IT-E165A / IT-E165B



IT-E165A is an optional anti-reverse protection module, suitable for IT6000B, IT6000C, IT6000D, IT8000 series products.



IT-E165B is an optional anti electromotive force module, suitable for IT6000B, IT6000C, IT6000D series instruments.

Model	Voltage	Current
IT-E165A-250	750V	250A
IT-E165A-400	750V	400A
IT-E165A-400	900V	400A

Model	Voltage	Current
IT-E165B	1200V	200A

AC electronic load

IT8200 Regenerative AC/DC Electronic Load

P05

Model	Specification
IT8203-350-30U	350 V/30 A/3 kVA/1Φ
IT8205-350-30U	350 V/30 A/5 kVA/1Φ
IT8206-350-90	350 V/90 A/6kVA/1Φ or 3Φ
IT8209-350-90	350 V/90 A/9kVA/1Φ or 3Φ
IT8212-350-90	350 V/90 A/12kVA/1Φ or 3Φ
IT8215-350-90	350 V/90 A/15kVA/1Φ or 3Φ
IT8230-350-180	350 V/180 A/30kVA/1Φ or 3Φ
IT8245-350-270	350 V/270 A/45kVA/1Φ or 3Φ
IT8260-350-360	350 V/360 A/60kVA/1Φ or 3Φ
IT8275-350-450	350 V/450 A/75kVA/1Φ or 3Φ
IT8290-350-540	350 V/540 A/90kVA/1Φ or 3Φ
IT82105-350-630	350 V/630 A/105kVA/1Φ or 3Φ
IT82120-350-720	350 V/720 A/120kVA/1Φ or 3Φ
IT82135-350-810	350 V/810 A/135kVA/1Φ or 3Φ
IT82150-350-900	350 V/900 A/150kVA/1Φ or 3Φ
IT82165-350-990	350 V/990 A/165kVA/1Φ or 3Φ
IT8230M-350-180	350 V/180 A/30kVA/1Φ or 3Φ
IT8245M-350-270	350 V/270 A/45kVA/1Φ or 3Φ
IT8260M-350-360	350 V/360 A/60kVA/1Φ or 3Φ
IT8275M-350-450	350 V/450 A/75kVA/1Φ or 3Φ
IT8290M-350-540	350 V/540 A/90kVA/1Φ or 3Φ
IT82105M-350-630	350 V/630 A/105kVA/1Φ or 3Φ
IT82120M-350-720	350 V/720 A/120kVA/1Φ or 3Φ
IT82135M-350-810	350 V/810 A/135kVA/1Φ or 3Φ
IT82150M-350-900	350 V/900 A/150kVA/1Φ or 3Φ
IT82165M-350-990	350 V/990 A/165kVA/1Φ or 3Φ

IT8600 AC/DC Electronic Load

Built-in communication interface: USB / LAN / front USB

P13

Model	Specification
IT8615	50~420Vrms/20Arms/1800VA/1Φ
IT8615L	15~260Vrms/20Arms/1800VA/1Φ
IT8616	50~420Vrms/40Arms/3600VA/1Φ
IT8617	50~420Vrms/60Arms/5400VA/1Φ or 3Φ
IT8624	50~420Vrms/80Arms/7200VA/1Φ
IT8625	50~420Vrms/100Arms/9000VA/1Φ
IT8626	50~420Vrms/120Arms/10.8kVA/1Φ
IT8627	50~420Vrms/140Arms/12.6kVA/1Φ
IT8628	50~420Vrms/160Arms/14.4kVA/1Φ

DC electronic load

IT-M3800 Regenerative DC Electronic Load

Built-in : USB/CAN/LAN/Digital I/O Optional: GPIB&RS232Analog

P16

Model	Specification
IT-M3801-10-120	10V / 120A / 1200W
IT-M3802-10-240	10V / 240A / 2400W
IT-M3803-10-360	10V / 360A / 3600W
IT-M3807-10-720	10V / 720A / 7200W
IT-M3802-32-80	32V / 80A / 2kW
IT-M3804-32-160	32V / 160A / 4kW
IT-M3806-32-240	32V / 240A / 6kW
IT-M3812-32-480	32V / 480A / 12kW
IT-M3802-80-40	80V / 40A / 2kW
IT-M3804-80-80	80V / 80A / 4kW
IT-M3806-80-120	80V / 120A / 6kW
IT-M3812-80-240	80V / 240A / 12kW
IT-M3802-300-20	300V / 20A / 2kW
IT-M3804-300-40	300V / 40A / 4kW
IT-M3806-300-60	300V / 60A / 6kW
IT-M3812-300-120	300V / 120A / 12kW
IT-M3802-500-12	500V / 12A / 2kW
IT-M3804-500-24	500V / 24A / 4kW
IT-M3806-500-36	500V / 36A / 6kW
IT-M3812-500-72	500V / 72A / 12kW
IT-M3802-800-8	800V / 8A / 2kW
IT-M3804-800-16	800V / 16A / 4kW
IT-M3806-800-24	800V / 24A / 6kW
IT-M3812-800-48	800V / 48A / 12kW
IT-M3806-1500-12	1500V / 12A / 6kW
IT-M3812-1500-24	1500V / 24A / 12kW

NEW

IT-M3800 Regenerative DC Electronic Load

Built-in : USB/CAN/LAN/Digital I/O Optional: GPIB&RS232Analog

P16

Model	Specification
IT-M3804-800-16	800V / 16A / 4kW
IT-M3806-800-24	800V / 24A / 6kW
IT-M3812-800-48	800V / 48A / 12kW
IT-M3806-1500-12	1500V / 12A / 6kW

IT-M3300 Regenerative DC Electronic Load

Optional communication interface: RS232/USB/CAN/LAN/RS485/GPIB

P22

Model	Specification
IT-M3312	60V/30A/200W
IT-M3322	60V/30A/400W
IT-M3332	60V/30A/800W
IT-M3313	150V/12A/200W
IT-M3323	150V/12A/400W
IT-M3333	150V/12A/800W
IT-M3314	300V/6A/200W
IT-M3324	300V/6A/400W
IT-M3334	300V/6A/800W
IT-M3315	600V/3A/200W
IT-M3325	600V/3A/400W
IT-M3335	600V/3A/800W

IT8000 Regenerative DC Electronic Load

Built-in communication interface: USB/CAN/LAN/Digital I/O

P28

Model	Specification
IT8005-80-150	80V/150A/5kW
IT8010-80-300	80V/300A/10kW
IT8015-80-450	80V/450A/15kW
IT8030-80-900	80V/900A/30kW
IT8045-80-1350	80V/1350A/45kW
IT8060-80-1800	80V/1800A/60kW
IT8075-80-2040	80V/2040A/75kW
IT8090-80-2040	80V/2040A/90kW
IT8105-80-2040	80V/2040A/105kW

IT8000 Regenerative DC Electronic Load

Built-in communication interface: USB/CAN/LAN/Digital I/O

P28

Model	Specification
IT8120-80-2040	80V/2040A/120kW
IT8006-300-75	300V/75A/6kW
IT8012-300-150	300V/150A/12kW
IT8018-300-225	300V/225A/18kW
IT8036-300-450	300V/450A/36kW
IT8054-300-675	300V/675A/54kW
IT8072-300-900	300V/900A/72kW
IT8090-300-1125	300V/1125A/90kW
IT8108-300-1350	300V/1350A/108kW
IT8126-300-1575	300V/1575A/126kW
IT8144-300-1800	300V/1800A/144kW
IT8006-500-40	500V/40A/6kW
IT8012-500-80	500V/80A/12kW
IT8018-500-120	500V/120A/18kW
IT8036-500-240	500V/240A/36kW
IT8054-500-360	500V/360A/54kW
IT8072-500-480	500V/480A/72kW
IT8090-500-600	500V/600A/90kW
IT8108-500-720	500V/720A/108kW
IT8126-500-840	500V/840A/126kW
IT8144-500-960	500V/960A/144kW
IT8006-800-25	800V/25A/ 6kW
IT8012-800-50	800V/50A/12kW
IT8018-800-75	800V/75A/18kW
IT8036-800-150	800V/150A/36kW
IT8054-800-225	800V/225A/54kW
IT8072-800-300	800V/300A/72kW
IT8090-800-375	800V/375A/90kW
IT8108-800-450	800V/450A/108kW
IT8126-800-525	800V/525A/126kW
IT8144-800-600	800V/600A/144kW



IT8000 Regenerative DC Electronic Load		P28
Built-in communication interface: USB/CAN/LAN/Digital I/O		
Model	Specification	
IT8018-1500-40	1500V/40A/18kW	
IT8036-1500-80	1500V/80A/36kW	
IT8054-1500-120	1500V/120A/54kW	
IT8072-1500-160	1500V/160A/72kW	
IT8090-1500-200	1500V/200A/90kW	
IT8108-1500-240	1500V/240A/108kW	
IT8126-1500-280	1500V/280A/126kW	
IT8144-1500-320	1500V/320A/144kW	
IT8018-2250-25	2250V/25A/18kW	
IT8036-2250-50	2250V/50A/36kW	
IT8054-2250-75	2250V/75A/54kW	
IT8072-2250-100	2250V/100A/72kW	
IT8090-2250-125	2250V/125A/90kW	
IT8108-2250-150	2250V/150A/108kW	
IT8126-2250-175	2250V/175A/126kW	
IT8144-2250-200	2250V/200A/144kW	

IT8700P+ High Speed Multi-channel DC Electronic Load		P32
Built-in communication interface: RS232/USB/GPIB/LAN		
Model	Specification	
IT8721P+	150 V/ 20 A/ 2 x 100 W	NEW
IT8731P+	150 V/ 40 A/ 200 W	NEW
IT8732P+	150 V/ 60 A/ 400 W	NEW
IT8722P+	150 V/ 20 A/ 2 x 250 W	NEW
IT8723P+	150 V/ 45 A/ 2 x 300 W	NEW
IT8733P+	150 V/ 120 A/ 600 W	NEW
IT8732BP+	600 V/ 20 A/ 300 W	NEW
IT8733BP+	600 V/ 30 A/ 500 W	NEW
IT8722BP+	600 V/ 15 A/ 2 x 250 W	NEW
IT8701P	Mainframe for 2 modules (including three interfaces)	NEW
IT8702P	Mainframe for 4 modules (including three interfaces)	NEW
IT8703P	Expansion mainframe for 4 modules	NEW

IT8700P Multi-channel Programmable DC Electronic Load		P36
Main frame has built-in communication interface: RS232 / USB / LAN		
Model	Specification	
IT8731P	80V/40A/200W	
IT8732P	80V/60A/400W	
IT8732BP	500V/20A/300W	
IT8733P	80V/120A/600W	
IT8733BP	500V/30A/500W	
IT8722P	80V/20A/250W*2	
IT8722BP	500V/15A/250W*2	
IT8723P	80V/45A/300W*2	
IT8701P	Two-load module main control unit	
IT8702P	Four-load module main control unit	
IT8703P	Four-load module expansion unit	

*1 IT8722P/IT8722BP two-way total power is 300W, the two-way simultaneous work need to meet: $50W \leq PCH1/PCH2 \leq 250W$; $PCH1+PCH2 \leq 300W$

*2 IT8700P modules should be equipped with IT8702P mainframe.

IT8700 Multi-channel Programmable DC Electronic Load		P40
Main frame has built-in communication interface: RS232 / USB / LAN		
Model	Specification	
IT8731	80V/40A/200W	
IT8732	80V/60A/400W	
IT8732B	500V/20A/300W	
IT8733	80V/120A/600W	
IT8733B	500V/30A/500W	
IT8722	80V/20A/250W*2	
IT8722B	500V/15A/250W*2	
IT8723	80V/45A/300W*2	
IT8701	Two-load module main control unit	
IT8702	Four-load module main control unit	
IT8703	Four-load module expansion unit	

*1 IT8722/IT8722B two-way total power is 300W, the two-way simultaneous work need to meet: $50W \leq PCH1/PCH2 \leq 250W$; $PCH1+PCH2 \leq 300W$

*2 IT8700 modules should be equipped with IT8702 mainframe

IT8400 High performance DC electronic load		P42
Built-in standard LAN, USB, RS232, GPIB, CAN and analog, IO interface		
Model	Specification	
IT8406-600-150	600 V/ 150 A/ 6 kW	
IT8406-1200-75	1200 V/ 75 A/ 6 kW	
IT8412-600-300	600 V/ 300 A/ 12 kW	
IT8412-1200-150	1200 V/ 150 A/ 12 kW	
IT8418-600-450	600 V/ 450 A/ 18 kW	
IT8418-1200-225	1200 V/ 225 A/ 18 kW	
IT8424-600-600	600 V/ 600 A/ 24 kW	
IT8424-1200-300	1200 V/ 300 A/ 24 kW	
IT8430-600-750	600 V/ 750 A/ 30 kW	
IT8430-1200-375	1200 V/ 375 A/ 30 kW	
IT8436-600-900	600 V/ 900 A/ 36 kW	
IT8436-1200-450	1200 V/ 450 A/ 36 kW	
IT8442-600-1050	600 V/ 1050 A/ 42 kW	
IT8442-1200-525	1200 V/ 525 A/ 42 kW	
IT8448-600-1200	600 V/ 1200 A/ 48 kW	
IT8448-1200-600	1200 V/ 600 A/ 48 kW	
IT8454-600-1350	600 V/ 1350 A/ 54 kW	
IT8454-1200-675	1200 V/ 675 A/ 54 kW	

IT8900A/E High Power DC Electronic Load		P48
Built-in communication interface: USB / GPIB / RS232 / LAN/CAN		
Model	Specification	
IT8902A-150-200	150V/200A/2kW	
IT8902E-150-200	150V/200A/2kW	
IT8902A-600-140	600V/140A/2kW	
IT8902E-600-140	600V/140A/2kW	
IT8902A-1200-80	1200V/80A/2kW	
IT8902E-1200-80	1200V/80A/2kW	
IT8904A-150-400	150V/400A/4kW	
IT8904E-150-400	150V/400A/4kW	
IT8904A-600-280	600V/280A/4kW	
IT8904E-600-280	600V/280A/4kW	
IT8904A-1200-160	1200V/160A/4kW	
IT8904E-1200-160	1200V/160A/4kW	
IT8906A-150-600	150V/600A/6kW	
IT8906E-150-600	150V/600A/6kW	
IT8906A-600-420	600V/420A/6kW	
IT8906E-600-420	600V/420A/6kW	
IT8906A/E-1200-240	1200V/240A/6kW	
IT8912A/E-150-1200	150V/1200A/12kW	
IT8912A/E-600-840	600V/840A/12kW	
IT8912A/E-1200-480	1200V/480A/12kW	
IT8918A/E-150-1800	150V/1800A/18kW	
IT8918A/E-600-1260	600V/1260A/18kW	
IT8918A/E-1200-720	1200V/720A/18kW	
IT8924A/E-150-2400	150V/2400A/24kW	
IT8924A/E-600-1680	600V/1680A/24kW	
IT8924A/E-1200-960	1200V/960A/24kW	
IT8930A/E-150-2400	150V/2400A/30kW	
IT8930A/E-600-2100	600V/2100A/30kW	
IT8930A/E-1200-2100	1200V/1200A/30kW	
IT8936A/E-150-2400	150V/2400A/36kW	
IT8936A/E-600-2400	600V/2400A/36kW	
IT8936A/E-1200-1440	1200V/1440A/36kW	
IT8942A/E-1 50-2400	150V/2400A/42kW	
IT8942A/E-600-2400	600V/2400A/42kW	
IT8942A/E-1200-1680	1200V/1680A/42kW	
IT8948A/E-150-2400	150V/2400A/48kW	
IT8948A/E-600-2400	600V/2400A/48kW	
IT8948A/E-1200-1920	1200V/1920A/48kW	
IT8954A/E-150-2400	150V/2400A/54kW	
IT8954A/E-600-2400	600V/2400A/54kW	
IT8954A/E-1200-2160	1200V/2160A/54kW	

IT8800 High Power DC Electronic Load

Built-in communication interface: USB / RS232 P52

Model	Specification
IT8811	120V/1 50W/30A/150W
IT8812	120V/30A/250W
IT8812B	500V/15A/200W
IT8812C	120V/60A/250W
IT8813	120V/60A/750W
IT8813C	120V/120A/750W
IT8813B	500V/30A/750W
IT8814	120V/120A/1500W
IT8814B	500V/60A/1200W
IT8816	120V/240A/3000W
IT8816B	500V/100A/2500W
IT8817	120V/360A/4500W
IT8817B	500V/120A/3600W
IT8818	120V/480A/6000W
IT8818B	500V/150A/5000W
IT8814C	120V/240A/1.5kW
IT8816C	120V/480A/3kW
IT8817C	120V/600A/4.5W

IT8912E High Accuracy DC Electronic Load

Built-in communication interface: USB / RS232 P57

Model	Specification
IT8912E	500V/15A/300W

IT8500G+ Programmable DC Electronic Load

Built-in communication interface: USB

Model	Specification
IT8511G+	150V / 30A / 150W (Standard USB)
IT8511AG+	150V / 30A / 150W (Standard USB)
IT8512G+	150V / 30A / 300W (Standard USB/LAN)
IT8512BG+	600V / 15A / 300W (Standard USB/LAN)

IT8500+ Programmable DC Electronic Load

Optional communication interface: RS485/RS232/USB

Model	Specification
IT8511+	120V/30A/150W
IT8511A+	150V/30A/150W
IT8511B+	500V/15A/150W
IT8512+	120V/30A/300W
IT8512A+	150V/30A/300W
IT8512B+	500V/1 5A/300W
IT8512C+	120V/60A/300W
IT8512H+	800V/5A/300W
IT8513A+	150V/60A/400W
IT8513C+	120V/120A/600W

Built-in communication interface: RS232/USB

Model	Specification
IT8514B+	500V/60A/1500W (Standard RS232/USB)
IT8514C+	120V/240A/1500W (Standard RS232/USB)
IT8516B+	120V/240A/3000W (Standard RS232/USB)

IT8200 Digital Control DC Electronic Load

Model	Specification
IT8211	60V/30A/150W

Programmable AC power supply

IT7900P High Performance Regenerative Grid Simulator P59

Model	Specification
IT7905P-350-30U	350V/30A/5kVA/1Φ
IT7906P-350-90	350V/90A/6kVA/1Φor3Φ
IT7909P-350-90	350V/90A/9kVA/1Φor3Φ
IT7912P-350-90	350V/90A/12kVA/1Φor3Φ
IT7915P-350-90	350V/90A/15kVA/1Φor3Φ
IT7930P-350-180	350V/180A/30kVA/1Φor3Φ
IT7945P-350-270	350V/270A/45kVA/1Φor3Φ
IT7960P-350-360	350V/360A/60kVA/1Φor3Φ
IT7975P-350-450	350V/450A/75kVA/1Φor3Φ
IT7990P-350-540	350V/540A/90kVA/1Φor3Φ

IT7900P High Performance Regenerative Grid Simulator P59

Model	Specification
IT79105P-350-630	350V/630A/105kVA/1Φor3Φ
IT79120P-350-720	350V/720A/120kVA/1Φor3Φ
IT79135P-350-810	350V/810A/135kVA/1Φor3Φ
IT79150P-350-900	350V/900A/150kVA/1Φor3Φ
IT79165P-350-990	350V/990A/165kVA/1Φor3Φ

IT7900 Regenerative Grid Simulator

Built-in : USB/CAN/LAN/Digital I/O Optional: GPIB&RS232&Analog P68

Model	Specification
IT7905-350-30	350V/30A/5kVA 1Φ
IT7906-350-90	350V/90A/6kVA 1Φ or 3Φ
IT7909-350-90	350V/90A/9kVA 1Φ or 3Φ
IT7912-350-90	350V/90A/12kVA 1Φ or 3Φ
IT7915-350-90	350V/90A/15kVA 1Φor 3Φ
IT7930-350-180	350V/180A/30kVA1Φ or 3Φ
IT7945-350-270	350V/270A/45kVA 1Φor 3Φ
IT7960-350-360	350V/360A/60kVA 1Φ or 3Φ
IT7975-350-450	350V/450A/75kVA 1Φor 3Φ
IT7990-350-540	350V/540A/90kVA 1Φ or 3Φ
IT79105-350-630	350V/630A/105kVA 1Φ or 3Φ
IT79120-350-720	350V/720A/120kVA 1Φ or 3Φ
IT79135-350-810	350V/810A/135kVA 1Φor 3Φ
IT79150-350-900	350V/900A/150kVA 1Φ or 3Φ
IT79165-350-990	350V/990A/165kVA1Φ or 3Φ

IT7800 High Power Programmable AC/DC Power Supply

Built-in : USB/CAN/LAN/Digital I/O Optional: GPIB&RS232&Analog P76

Model	Specification
IT7803-350-30U	350V/30A/3kVA 1Φ
IT7803J-350-30U	350V/30A/3kVA 1Φ
IT7805-350-30U	350V/30A/5kVA 1Φ
IT7806-350-90	350V/90A/6kVA 1Φ or 3Φ
IT7809-350-90	350V/90A/9kVA 1Φ or 3Φ
IT7812-350-90	350V/90A/12kVA 1Φor 3Φ
IT7815-350-90	350V/90A/15kVA 1Φor 3Φ
IT7830-350-180	350V/180A/30kVA1Φ or 3Φ
IT7845-350-270	350V/270A/45kVA 1Φor 3Φ
IT7860-350-360	350V/360A/60kVA 1Φ or 3Φ
IT7875-350-450	350V/450A/75kVA 1Φor 3Φ
IT7890-350-540	350V/540A/90kVA 1Φ or 3Φ
IT78105-350-630	350V/630A/105kVA 1Φ or 3Φ
IT78120-350-720	350V/720A/120kVA 1Φ or 3Φ
IT78135-350-810	350V/810A/135kVA 1Φor 3Φ
IT78150-350-900	350V/900A/150kVA 1Φ or 3Φ
IT78165-350-990	350V/990A/165kVA1Φ or 3Φ

IT-M7700 High Performance Programmable AC Power Supply

Optional communication interface: RS232/USB/CAN/LAN/RS485/GPIB P82

Model	Specification
IT-M7721	300V / 3A / 300VA
IT-M7722	300V / 6A / 600VA
IT-M7722E	300V / 10A / 1000VA
IT-M7723	300V / 12A / 1200VA
IT-M7723E	600V / 6A / 1200VA
IT-M7723E	300V / 15A / 1500VA
IT-M7724	300V / 30A / 3000VA
IT-M7724	600V / 15A / 3000VA

IT7600 high performance programmable AC power suppl

Built-in communication interface: USB/RS232/LAN/CAN 1 front USB P87

Model	Specification
IT7622	150V/300V/6A/750VA,1Φ
IT7624	150V/300V/12A/1500VA,1Φ
IT7625	150V/300V/36A/4500VA,1Φ or 3Φ
IT7626	150V/300V/24A/3000VA,1Φ



IT7300 Programmable AC Power Supply Built-in : USB/RS232/LAN		P92
Model	Specification	
IT7321	150V/300V,3A/1.5A,300VA,1φ	
IT7322	150V/300V,6A/3A, 50VA,1φ	
IT7324	150V/300V,12A/6A,500VA, φ	
IT7326	150V/300V,24A/12A,3000VA,1φ	
IT7322H	250V/500V,3A/1.5A, 50VA,1φ	
IT7324H	250V/500V,6A/3A,1500VA,1φ	
IT7326H	250V/500V,12A/6A,3000VA,1φ	
IT7322T	150V/300V,6A/3A,2250VA,3φ	
IT7324T	150V/300V,12A/6A,4500VA,3φ	
IT7326T	150V/300V,24A/12A,9000VA,3φ	
IT7322HT	250V/500V,3A/1.5A,2250VA,3φ	
IT7324HT	250V/500V,6A/3A,4500VA,3φ	
IT7326HT	250V/500V,12A/6A,9000VA,3φ	

Programmable DC power supply

IT-N2100 Series Solar Array Simulator		P94
Model	Specification	
IT-N2121	80V, 25A, 800W,solar array simulation software included	NEW
IT-N2123	150V, 10A, 800W,solar array simulation software included	NEW
IT-N2131	80V, 20A, 1500W,solar array simulation software included	NEW
IT-N2133	150V, 10A, 1500W,solar array simulation software included	NEW

IT-N6900 Programmable DC Power Supply Built-in : USB/LAN/Digital I/O		P98
Model	Specification	
IT-N6952	60V/25A/850W	NEW
IT-N6962	60V/25A/1500W	NEW
IT-N6953	150V/10A/850W	NEW
IT-N6963	150V/10A/1500W	NEW

IT-M3140 Series Programmable DC Power Supply Standard USB/LAN optional RS232 & analog, GPIB		P100
Model	Specification	
IT-M3141	30V / 150A / 3000W	NEW
IT-M3142	80V / 80A / 3000W	NEW
IT-M3143	150V / 40A / 3000W	NEW
IT-M3144	300V / 20A / 3000W	NEW
IT-M3145	600V / 10A / 3000W	NEW
IT-M3146	1000V / 6A / 3000W	NEW
IT-M3147	1200V / 5A / 3000W	NEW
IT-M3131E	30V / 150A / 1850W	NEW
IT-M3132E	80V / 80A / 1850W	NEW
IT-M3133E	150V / 40A / 1850W	NEW
IT-M3134E	300V / 20A / 1850W	NEW
IT-M3135E	600V / 10A / 1850W	NEW
IT-M3136E	1000V / 6A / 1850W	NEW
IT-M3137E	1200V / 5A / 1850W	NEW
IT-E158A	For 2 units installed side by side in ITECH standard cabinet	NEW
IT-E158B	For 2 units installed side by side in non-ITECH cabinet	NEW
IT-E158C	For single unit installed in ITECH standard cabinet	NEW
IT-E158D	For single unit installed in non-ITECH cabinet	NEW
IT-E176	GPIB communication card	NEW
IT-E177	RS232 & Analog card	NEW

IT-M3900B Regenerative Power system Built-in : USB/CAN/LAN/Digital I/O Optional:GPIB&RS232&Analog		P103
Model	Specification	
IT-M3901B-10-170	source: 10V / 170A / 1700W load: 10V / 120A / 1200W	
IT-M3903B-10-340	source: 10V / 340A / 3400W load: 10V / 240A / 2400W	
IT-M3905B-10-510	source: 10V / 510A / 5100W load: 10V / 360A / 3600W	
IT-M3910B-10-1020	source: 10V / 1020A / 10200W load: 10V / 720A / 7200W	
IT-M3902B-32-80	source: 32V / 80A / 2kW load: 32V / 80A / 2kW	
IT-M3904B-32-160	source: 32V / 160A / 4kW load: 32V / 160A / 4kW	
IT-M3906B-32-240	source: 32V / 240A / 6kW load: 32V / 240A / 6kW	
IT-M3912B-32-480	source: 32V / 480A / 12kW load: 32V / 480A / 12kW	
IT-M3902B-80-40	source: 80V / 40A / 2kW load: 80V / 40A / 2kW	
IT-M3904B-80-80	source: 80V / 80A / 4kW load: 80V / 80A / 4kW	
IT-M3906B-80-120	source: 80V / 120A / 6kW load: 80V / 120A / 6kW	
IT-M3912B-80-240	source: 80V / 240A / 12kW load: 80V / 240A / 12kW	

IT-M3900B Regenerative Power system Built-in : USB/CAN/LAN/Digital I/O Optional:GPIB&RS232&Analog		P103
Model	Specification	
IT-M3902B-300-20	source: 300V / 20A / 2kW load: 300V / 20A / 2kW	
IT-M3904B-300-40	source: 300V / 40A / 4kW load: 300V / 40A / 4kW	
IT-M3906B-300-60	source: 300V / 60A / 6kW load: 300V / 60A / 6kW	
IT-M3912B-300-120	source: 300V / 120A / 12kW load: 300V / 120A / 12kW	
IT-M3902B-500-12	source: 500V / 12A / 2kW load: 500V / 12A / 2kW	
IT-M3904B-500-24	source: 500V / 24A / 4kW load: 500V / 24A / 4kW	
IT-M3906B-500-36	source: 500V / 36A / 6kW load: 500V / 36A / 6kW	
IT-M3912B-500-72	source: 500V / 72A / 12kW load: 500V / 72A / 12kW	
IT-M3902B-800-8	source: 800V / 8A / 2kW load: 800V / 8A / 2kW	
IT-M3904B-800-16	source: 800V / 16A / 4kW load: 800V / 16A / 4kW	
IT-M3906B-800-24	source: 800V / 24A / 6kW load: 800V / 24A / 6kW	
IT-M3912B-800-48	source: 800V / 48A / 12kW load: 800V / 48A / 12kW	
IT-M3906B-1500-12	source: 1500V / 12A / 6kW load: 1500V / 12A / 6kW	
IT-M3912B-1500-24	source: 1500V / 24A / 12kW load: 1500V / 24A / 12kW	NEW

IT-M3900C Bidirectional Programmable DC Power Supply Built-in : USB/CAN/LAN/Digital I/O Optional:GPIB&RS232&Analog		P108
Model	Specification	
IT-M3901C-10-170	10V / 170A / 1700W	
IT-M3903C-10-340	10V / 340A / 3400W	
IT-M3905C-10-510	10V / 510A / 5100W	
IT-M3910C-10-1020	10V / 1020A / 10200W	
IT-M3902C-32-80	32V / 80A / 2kW	
IT-M3904C-32-160	32V / 160A / 4kW	
IT-M3906C-32-240	32V / 240A / 6kW	
IT-M3912C-32-480	32V / 480A / 12kW	
IT-M3902C-80-40	80V / 40A / 2kW	
IT-M3904C-80-80	80V / 80A / 4kW	
IT-M3906C-80-120	80V / 120A / 6kW	
IT-M3912C-80-240	80V / 240A / 12kW	
IT-M3902C-85-40SAS	85V / 40A / 2kW	NEW
IT-M3904C-85-80SAS	85V / 80A / 4kW	NEW
IT-M3906C-85-120SAS	85V / 120A / 6kW	NEW
IT-M3901C-150-25PV	150V / 25A / 1.5kW	NEW
IT-M3903C-150-50PV	150V / 50A / 3kW	NEW
IT-M3902C-300-20	300V / 20A / 2kW	
IT-M3904C-300-40	300V / 40A / 4kW	
IT-M3906C-300-60	300V / 60A / 6kW	
IT-M3912C-300-120	300V / 120A / 12kW	
IT-M3902C-500-12	500V / 12A / 2kW	
IT-M3904C-500-24	500V / 24A / 4kW	
IT-M3906C-500-36	500V / 36A / 6kW	
IT-M3912C-500-72	500V / 72A / 12kW	
IT-M3902C-500-12	800V / 8A / 2kW	
IT-M3904C-500-24	800V / 16A / 4kW	
IT-M3906C-500-36	800V / 24A / 6kW	
IT-M3912C-500-72	800V / 48A / 12kW	
IT-M3906C-1500-12	1500V / 12A / 6kW	
IT-M3912C-1500-24	1500V / 24A / 12kW	NEW

IT-M3900D High power DC power supply Built-in : USB/CAN/LAN/Digital I/O Optional:GPIB&RS232&Analog		P113
Model	Specification	
IT-M3901D-10-170	10V / 170A / 1700W	
IT-M3903D-10-340	10V / 340A / 3400W	
IT-M3905D-10-510	10V / 510A / 5100W	
IT-M3910D-10-1020	10V / 1020A / 10200W	
IT-M3902D-32-80	32V / 80A / 2kW	
IT-M3904D-32-160	32V / 160A / 4kW	
IT-M3906D-32-240	32V / 240A / 6kW	
IT-M3912D-32-480	32V / 480A / 12kW	
IT-M3902D-80-40	80V / 40A / 2kW	
IT-M3904D-80-80	80V / 80A / 4kW	
IT-M3906D-80-120	80V / 120A / 6kW	
IT-M3912D-80-240	80V / 240A / 12kW	
IT-M3902D-300-20	300V / 20A / 2kW	
IT-M3904D-300-40	300V / 40A / 4kW	
IT-M3906D-300-60	300V / 60A / 6kW	
IT-M3912D-300-120	300V / 120A / 12kW	
IT-M3902D-500-12	500V / 12A / 2kW	
IT-M3904D-500-24	500V / 24A / 4kW	
IT-M3906D-500-36	500V / 36A / 6kW	
IT-M3912D-500-72	500V / 72A / 12kW	
IT-M3902D-800-12	800V / 8A / 2kW	
IT-M3904D-800-24	800V / 16A / 4kW	
IT-M3906D-800-36	800V / 24A / 6kW	
IT-M3912D-800-72	800V / 48A / 12kW	
IT-M3906D-1500-12	1500V / 12A / 6kW	
IT-M3912D-1500-24	1500V / 24A / 12kW	NEW

IT-M3100 Ultra-compact Wide Range DC Power Supply		P119
Optional communication interface: RS232/USB/CAN/LAN/RS485/GPIB		
Model	Specification	
IT-M3110	20V/100A/400W	
IT-M3120	20V/100A/850W	
IT-M3111	30V/70A/400W	
IT-M3121	30V/70A/850W	
IT-M3112	80V/22A/400W	
IT-M3122	80V/22A/850W	
IT-M3113	150V/12A/400W	
IT-M3123	150V/12A/850W	
IT-M3114	300V/6A/400W	
IT-M3124	300V/6A/850W	
IT-M3115	600V/3A/400W	
IT-M3125	600V/3A/850W	

IT-M3100D Dual-channel DC Power Supply		P123
Model	Specification	
IT-M3131D	CH1:30V/15A/200W; CH2:30V/15A/200W	
IT-M3141D	CH1:30V/15A/400W; CH2:30V/15A/400W	
IT-M3132D	CH1:60V/10A/200W; CH2:60V/10A/200W	
IT-M3142D	CH1:60V/10A/400W; CH2:60V/10A/400W	

IT-M3200 High-precision Programmable dC power		P127
Optional communication interface: RS232/USB/CAN/LAN/RS485/GPIB		
Model	Specification	
IT-M3223	60V/10A/100W	
IT-M3233	60V/10A/200W	
IT-M3243	60V/10A/360W	
IT-M3253	20V/20A/100W	
IT-M3263	20V/20A/200W	
IT-M3273	20V/20A/360W	

IT-M3400 Bidirectional DC Power Supply		P132
Optional communication interface: RS232/USB/CAN/LAN/RS485/GPIB		
Model	Specification	
IT-M3412	60V/30A/200W	
IT-M3422	60V/30A/400W	
IT-M3432	60V/30A/800W	
IT-M3413	150V/12A/200W	
IT-M3423	150V/12A/400W	
IT-M3433	150V/12A/800W	
IT-M3414	300V/6A/200W	
IT-M3424	300V/6A/400W	
IT-M3434	300V/6A/800W	
IT-M3415	600V/3A/200W	
IT-M3425	600V/3A/400W	
IT-M3435	600V/3A/800W	

IT-M3600 Regenerative Power System		P138
Optional communication interface: RS232/USB/CAN/LAN/RS485/GPIB		
Model	Specification	
IT-M3612	60V/30A/200W	
IT-M3622	60V/30A/400W	
IT-M3632	60V/30A/800W	
IT-M3613	150V/12A/200W	
IT-M3623	150V/12A/400W	
IT-M3633	150V/12A/800W	
IT-M3614	300V/6A/200W	
IT-M3624	300V/6A/400W	
IT-M3634	300V/6A/800W	
IT-M3615	600V/3A/200W	
IT-M3625	600V/3A/400W	
IT-M3635	600V/3A/800W	

IT6000B Regenerative Power System		P144
Built-in communication interface: USB/CAN/LAN/Digital I/O		
Model	Specification	
IT6005B-80-150	80V/150A/5kW	
IT6010B-80-300	80V/300A/10kW	
IT6015B-80-450	80V/450A/15kW	
IT6030B-80-900	80V/900A/30kW	
IT6045B-80-1350	80V/1350A/45kW	
IT6060B-80-1800	80V/1800A/60kW	
IT6075B-80-2040	80V/2040A/75kW	
IT6090B-80-2040	80V/2040A/90kW	
IT6105B-80-2040	80V/2040A/105kW	
IT6120B-80-2040	80V/2040A/120kW	
IT6006B-300-75	300V/75A/6kW	
IT6012B-300-150	300V/150A/12kW	
IT6018B-300-225	300V/225A/18kW	
IT6036B-300-450	300V/450A/36kW	
IT6054B-300-675	300V/675A/54kW	
IT6072B-300-900	300V/900A/72kW	
IT6090B-300-1125	300V/1125A/90kW	
IT6108B-300-1350	300V/1350A/108kW	
IT6126B-300-1575	300V/1575A/126kW	
IT6144B-300-1800	300V/1800A/144kW	
IT6006B-500-40	500V/40A/6kW	
IT6012B-500-80	500V/80A/12kW	
IT6018B-500-120	500V/120A/18kW	
IT6036B-500-240	500V/240A/36kW	
IT6054B-500-360	500V/360A/54kW	
IT6072B-500-480	500V/480A/72kW	
IT6090B-500-600	500V/600A/90kW	
IT6108B-500-720	500V/720A/108kW	
IT6126B-500-840	500V/840A/126kW	
IT6144B-500-960	500V/960A/144kW	
IT6006B-800-25	800V/25A/6kW	
IT6012B-800-50	800V/50A/12kW	
IT6018B-800-75	800V/75A/18kW	
IT6036B-800-150	800V/150A/36kW	
IT6054B-800-225	800V/225A/54kW	
IT6072B-800-300	800V/300A/72kW	
IT6090B-800-375	800V/375A/90kW	
IT6108B-800-450	800V/450A/108kW	
IT6126B-800-525	800V/525A/126kW	
IT6144B-800-600	800V/600A/144kW	
IT6018B-1500-40	1500V/40A/18kW	
IT6036B-1500-80	1500V/80A/36kW	
IT6054B-1500-120	1500V/120A/54kW	
IT6072B-1500-160	1500V/160A/72kW	
IT6090B-1500-200	1500V/200A/90kW	
IT6108B-1500-240	1500V/240A/108kW	
IT6126B-1500-280	1500V/280A/126kW	
IT6144B-1500-320	1500V/320A/144kW	
IT6018B-2250-25	2250V/25A/18kW	
IT6036B-2250-50	2250V/50A/36kW	
IT6054B-2250-75	2250V/75A/54kW	
IT6072B-2250-100	2250V/100A/72kW	
IT6090B-2250-125	2250V/125A/90kW	
IT6108B-2250-150	2250V/150A/108kW	
IT6126B-2250-175	2250V/175A/126kW	
IT6144B-2250-200	2250V/200A/144kW	



IT6000C Bidirectional Programmable DC Power Supply
Built-in communication interface: USB/CAN/LAN/Digital I/O **P151**

Model	Specification
IT6005C-80-150	80V/150A/5kW
IT6010C-80-300	80V/300A/10kW
IT6015C-80-450	80V/450A/15kW
IT6030C-80-900	80V/900A/30kW
IT6045C-80-1350	80V/1350A/45kW
IT6060C-80-1800	80V/1800A/60kW
IT6075C-80-2040	80V/2040A/75kW
IT6090C-80-2040	80V/2040A/90kW
IT6105C-80-2040	80V/2040A/105kW
IT6120C-80-2040	80V/2040A/120kW
IT6006C-300-75	300V/75A/6kW
IT6012C-300-150	300V/150A/12kW
IT6018C-300-225	300V/225A/18kW
IT6036C-300-450	300V/450A/36kW
IT6054C-300-675	300V/675A/54kW
IT6072C-300-900	300V/900A/72kW
IT6090C-300-1125	300V/1125A/90kW
IT6108C-300-1350	300V/1350A/108kW
IT6126C-300-1575	300V/1575A/126kW
IT6144C-300-1800	300V/1800A/144kW
IT6006C-500-40	500V/40A/6kW
IT6012C-500-80	500V/80A/12kW
IT6018C-500-120	500V/120A/18kW
IT6036C-500-240	500V/240A/36kW
IT6054C-500-360	500V/360A/54kW
IT6072C-500-480	500V/480A/72kW
IT6090C-500-600	500V/600A/90kW
IT6108C-500-720	500V/720A/108kW
IT6126C-500-840	500V/840A/126kW
IT6144C-500-960	500V/960A/144kW
IT6006C-800-25	800V/25A/6kW
IT6012C-800-50	800V/50A/12kW
IT6018C-800-75	800V/75A/18kW
IT6036C-800-150	800V/150A/36kW
IT6054C-800-225	800V/225A/54kW
IT6072C-800-300	800V/300A/72kW
IT6090C-800-375	800V/375A/90kW
IT6108C-800-450	800V/450A/108kW
IT6126C-800-525	800V/525A/126kW
IT6144C-800-600	800V/600A/144kW
IT6018C-1500-40	1500V/40A/18kW
IT6036C-1500-80	1500V/80A/36kW
IT6054C-1500-120	1500V/120A/54kW
IT6072C-1500-160	1500V/160A/72kW
IT6090C-1500-200	1500V/200A/90kW
IT6108C-1500-240	1500V/240A/108kW
IT6126C-1500-280	1500V/280A/126kW
IT6144C-1500-320	1500V/320A/144kW
IT6018C-2250-25	2250V/25A/18kW
IT6036C-2250-50	2250V/50A/36kW
IT6054C-2250-75	2250V/75A/54kW
IT6072C-2250-100	2250V/100A/72kW
IT6090C-2250-125	2250V/125A/90kW
IT6108C-2250-150	2250V/150A/108kW
IT6126C-2250-175	2250V/175A/126kW
IT6144C-2250-200	2250V/200A/144kW

IT6000D High Power Programmable DC Power Supply
Built-in communication interface: USB/CAN/LAN/Digital I/O **P155**

Model	Specification
IT6005D-80-150	80V/150A/5kW
IT6010D-80-300	80V/300A/10kW
IT6015D-80-450	80V/450A/15kW
IT6030D-80-900	80V/900A/30kW
IT6045D-80-1350	80V/1350A/45kW
IT6060D-80-1800	80V/1800A/60kW
IT6075D-80-2040	80V/2040A/75kW
IT6090D-80-2040	80V/2040A/90kW
IT6105D-80-2040	80V/2040A/105kW
IT6120D-80-2040	80V/2040A/120kW
IT6006D-300-75	300V/75A/6kW
IT6012D-300-150	300V/150A/12kW
IT6018D-300-225	300V/225A/18kW
IT6036D-300-450	300V/450A/36kW
IT6054D-300-675	300V/675A/54kW
IT6072D-300-900	300V/900A/72kW
IT6090D-300-1125	300V/1125A/90kW
IT6108D-300-1350	300V/1350A/108kW
IT6126D-300-1575	300V/1575A/126kW
IT6144D-300-1800	300V/1800A/144kW
IT6006D-500-40	500V/40A/6kW
IT6012D-500-80	500V/80A/12kW
IT6018D-500-120	500V/120A/18kW
IT6036D-500-240	500V/240A/36kW
IT6054D-500-360	500V/360A/54kW
IT6072D-500-480	500V/480A/72kW
IT6090D-500-600	500V/600A/90kW
IT6108D-500-720	500V/720A/108kW
IT6126D-500-840	500V/840A/126kW
IT6144D-500-960	500V/960A/144kW
IT6006D-800-25	1500V/40A/18kW
IT6012D-800-50	1500V/80A/36kW
IT6018D-800-75	1500V/120A/54kW
IT6036D-800-150	1500V/160A/72kW
IT6054D-800-225	1500V/200A/90kW
IT6072D-800-300	1500V/240A/108kW
IT6090D-800-375	1500V/280A/126kW
IT6108D-800-450	1500V/320A/144kW
IT6126D-800-525	2250V/25A/18kW
IT6144D-800-600	2250V/50A/36kW
IT6018D-1500-40	2250V/75A/54kW
IT6036D-1500-80	2250V/100A/72kW
IT6054D-1500-120	2250V/125A/90kW
IT6072D-1500-160	2250V/150A/108kW
IT6090D-1500-200	2250V/175A/126kW
IT6108D-1500-240	2250V/200A/144kW
IT6126D-1500-280	800V/25A/6kW
IT6144D-1500-320	800V/50A/12kW
IT6018D-2250-25	800V/75A/18kW
IT6036D-2250-50	800V/150A/36kW
IT6054D-2250-75	800V/225A/54kW
IT6072D-2250-100	800V/300A/72kW
IT6090D-2250-125	800V/375A/90kW
IT6108D-2250-150	800V/450A/108kW
IT6126D-2250-175	800V/525A/126kW
IT6144D-2250-200	800V/600A/144kW

IT6400 Bipolar DC Power Supply / Battery Simulator Built-in communication interface: USB / LAN / front USB		P157
Model	Specification	
IT6402	CH1: -6V~0V,0~6V CH1: ±2A CH1: 12W CH2: 0~6V CH2: ±2A CH2: 12W	
IT6411	±15V/±9V/±3A/±5A/45W	
IT6411S	-15V~0V,0~15V/±0.1A/1.5W	
IT6412	CH1: ±15V/±9V CH1: ±3A/±5A CH1: 45W CH2: 0~15V/0~9V CH2: ±3A/±5A CH1: 45W	
IT6412S	CH1: -15V~0V,0~15V CH1: ±0.1A/1.5W CH1: 1.5W CH2: 0~15V CH2: ±0.1A/1.5W CH2: 1.5W	
IT6431	-15V~0V,0~15V/±10A/150W	
IT6432	-30V~0V,0~30V/±5A/150W	
IT6432S	-30V~0V,0~30V/±21mA/0.63W	
IT6433	-60V~0V,0~60V/±2.5 A/150W	

IT6500 Wide-range High-power DC Power Supply Built-in communication interface: USB / RS232 / RS485		P159
Model	Specification	
IT6502D	80V/60A/800W	
IT6512	80V/60A/1200W (Support List, DIN waveforms)	
IT6512A	80V/60A/1200W	
IT6513	150V/30A/1200W (Support List, DIN waveforms)	
IT6513A	150V/30A/1200W	

IT6500 Wide-range High-power DC Power Supply Built-in communication interface: USB / RS232 / CAN / LAN		P159
Model	Specification	
IT6512C	80V/120A/1800W	
IT6512D	80V/120A/1800W	
IT6513C	200V/60A/1800W	
IT6513D	200V/60A/1800W	
IT6514C	360V/30A/1800W	
IT6514D	360V/30A/1800W	
IT6515C	500V/20A/1800W	
IT6515D	500V/20A/1800W	
IT6516C	750V/15A/1800W	
IT6516D	750V/15A/1800W	
IT6517C	1000V/10A/1800W	
IT6517D	1000V/10A/1800W	
IT6522C	80V/120A/3kW	
IT6522D	80V/120A/3kW	
IT6523C	200V/60A/3kW	
IT6523D	200V/60A/3kW	
IT6524C	360V/30A/3kW	
IT6524D	360V/30A/3kW	
IT6525C	500V/20A/3kW	
IT6525D	500V/20A/3kW	
IT6526C	750V/15A/3kW	
IT6526D	750V/15A/3kW	
IT6527C	1000V/10A/3kW	
IT6527D	1000V/10A/3kW	
IT6532C	80V/240A/6kW	
IT6532D	80V/240A/6kW	
IT6533C	200V/120A/6kW	
IT6533D	200V/120A/6kW	
IT6534C	360V/60A/6kW	
IT6534D	360V/60A/6kW	
IT6535C	500V/40A/6kW	
IT6535D	500V/40A/6kW	
IT6536C	750V/30A/6kW	
IT6536D	750V/30A/6kW	
IT6537C	1000V/20A/6kW	
IT6537D	1000V/20A/6kW	

*1 IT6500C is high speed multi-function DC power supply, IT6500D is stable multi-function DC power supply

IT6900B Wide -range Programmable DC Power Supply Built-in communication interface: USB / RS232		P163
Model	Specification	
IT6922A	60V/5A/100W	
IT6932A	60V/10A/200W	
IT6933A	150V/5A/200W	
IT6942A	60V/15A/360W	
IT6952A	60V/25A/600W	
IT6953A	150V/10A/600W	
Built-in communication interface: USB / RS232 / RS485 / external analog		
Model	Specification	
IT6922B	60V/5A/100W	
IT6932B	60V/10A/200W	
IT6942B	60V/15A/360W	
IT6952B	60V/25A/600W	
IT6953B	150V/10A/600W	

IT6800A/B Single Channel Programmable DC Power Supply Built-in communication interface: RS232 / USB		P165
Model	Specification	
IT6831A	18V/10A/180W	
IT6832A	32V/6A/192W	
IT6833A	72V/3A/216W	
IT6835A	50V/4A/200W	

IT6800A/B Single Channel Programmable DC Power Supply Built-in communication interface: RS232 / USB / GPIB		
Model	Specification	
IT6832B	32V/6A/192W	
IT6833B	72V/3A/216W	
IT6835B	50V/4A/200W	

IT6800A / B Dual range programmable DC power supply Built-in communication interface: RS232 / USB		
Model	Specification	
IT6861A	20V/5A/100W 8V/9A/72W	
IT6862A	32V/3A/96W 12V/6A/72W	
IT6863A	72V/1.5A/108W 32V/3A/96W	
IT6872A	35V/4A/140W 15V/7A/105W	
IT6873A	0-75V,2A/0-32V,4A	
IT6874A	0-150V,1.2A/0-60V,2A	

Built-in communication interface: RS232 / USB / GPIB		
Model	Specification	
IT6861B	20V/5A/100W 8V/9A/72W	
IT6862B	32V/3A/96W 12V/6A/72W	
IT6863B	72V/1.5A/108W 32V/3A/96W	
IT6872B	35V/4A/140W 15V/7A/105W	
IT6873B	75V/2A/150W 32V/4A/128W	
IT6874B	150V/1.2A/180W 60V/2A/120W	

IT6800 High Performance DC Power Supply Optional communication interface: GPIB / RS232 / USB		
Model	Specification	
IT6821	18V/5A/90W	
IT6822	32V/3A/96W	
IT6823	72V/1.5A/108W	
IT6831	18V/10A/180W	
IT6832	32V/6A/192W	
IT6833	72V/3A/216W	
IT6834	150V/1.2A/180W	



IT6700H High Voltage DC Power Supply Built-in communication interface: USB / RS232 P167

Model	Specification
IT6722	80V/20A/400W, with GPIB
IT6722A	80V/20A/400W
IT6723B	150V/20A/850W
IT6723C	32V/110A/850W
IT6723	80V/40A/850W
IT6723G	600V/5A/850W
IT6723H	300V/10A/850W
IT6724C	32V/110A/1500W
IT6724	80V/40A/1500W
IT6724B	150V/20A/1500W
IT6724H	300V/10A/1500W
IT6724G	600V/5A/1500W
IT6726B	160V/40A/3KW
IT6726C	32V/220A/3KW
IT6726H	300V/20A/3KW
IT6726G	600V/10A/3KW
IT6726V	1200V/5A/3KW

IT6700 DC Power Supply

Model	Specification
IT6720	60V/5A/100W
IT6721	60V/8A/180W

IT6100B High Accuracy DC Power Supply Built-in communication interface: USB / RS232 P169

Model	Specification
IT6121B	20V/5A/100W
IT6122B	32V/3A/96W
IT6123B	72V/1.2A/86W
IT6132B	30V/5A/150W
IT6133B	60V/2.5A/150W
IT6162B	20V/50A/1000W
IT6164B	30V/40A/1200W 60V/20A/1200W

IT6100 DC Power Supply Optional communication interface: USB / RS232 / GPIB P170

Model	Specification
IT6151	5.2V/60A/312W
IT6152	20V/27A/540W
IT6153	30V/18A/540W
IT6154	60V/9A/540W

IT6300 Triple Channels DC power supply P171

Model	Specification
IT6302	30V/3A/90W*2CH Optional communication interface: USB/RS232
	5V/3A/15W*1CH Optional communication interface: USB/RS232
IT6322	30V/3A/90W*2CH Optional communication interface: USB/GPIB/RS232
	5V/3A/15W*1CH Optional communication interface: USB/GPIB/RS232

Built-in communication interface: USB / RS232

Model	Specification
IT6322A	30V/3A/90W*2CH 5V/3A/15W*1CH
IT6332A	30V/6A/180W*2CH 5V/3A/15W*1CH
IT6333A	60V/3A/180W*2CH 5V/3A/15W*1CH

Built-in communication interface: USB / RS232 / GPIB

Model	Specification
IT6322B	30V/3A/90W*2CH 5V/3A/15W*1CH
IT6332B	30V/6A/180W*2CH 5V/3A/15W*1CH
IT6333B	60V/3A/180W*2CH 5V/3A/15W*1CH

Built-in communication interface: USB / LAN

Model	Specification
IT6322C	30V/3A/90W*2CH 5V/3A/15W*1CH
IT6332C	30V/6A/180W*2CH 5V/3A/15W*1CH
IT6333C	60V/3A/180W*2CH 5V/3A/15W*1CH
IT6341C	6V/16A/80W*1CH 16V/5A/80W*1CH

Source Measure Unit P172

IT2800 Graphical Source Measure Unit
Built-in communication interface: Digital IO/USB/LAN

Model	Specification
IT2801	1000V/1A/20W*1CH NEW
IT2805	200V/1.5A/20W*1CH NEW
IT2806	200V/3A DC/ 10A Pulse/20W*1CH NEW

Power meter P181

IT9100 Power Meter
Built-in communication interface: USB / RS232 / Ethernet
communication interface
Front USB interface

Model	Specification
IT9121	600V/20A AC power meter (with harmonic measurement)
IT9121C	600V/50A
IT9121E	600V/20A
IT9121H	1000V/20A
IT-E185	Power meter test fixture

Battery tester P183

IT5100 Battery tester
Built-in communication interface: USB / LAN // front USB interface

Model	Specification
IT5101	-300V~+300V/3mΩ~3000Ω
IT5101E	-300V~+300V/300mΩ~3Ω
IT5101H	-1000V~+1000V/3mΩ~3000Ω



Automotive Electronics Test Solutions



IT6000C Bidirectional
Programmable DC Power Supply



IT6500 Wide-range
High-power DC Power Supply



IT8900A/E High Performance
High Power DC Electronic Load



IT6400 Series Bipolar
DC Power Supply / Battery Simulator



IT-M3400 Bidirectional
DC Power Supply



EV Test Solutions



IT7900P Regenerative
Grid Simulator



IT6000C Bidirectional
Programmable DC Power Supply



IT8000 Series Regenerative
DC Electronic Load



Battery Test/ Simulation Solutions



ITS5300 Battery
Charge&Discharge Test System



IT6400 Series Bipolar
DC Power Supply / Battery Simulator




IT6000C Bidirectional
Programmable DC Power Supply



IT5100 Battery Tester



IT-M3900C Bidirectional
DC Power Supply



BSS2000 Battery Simulation Software
FCS3000 Fuel Cell Simulation Software



Semiconductor / IC Test Solutions



IT6400 Series Bipolar
DC Power Supply / Battery Simulator



IT6100B High Speed
High Precision Programmable
DC Power Supply



IT-M3200 High Precision
Programmable DC Power Supply



IT2800 Series
Power Meter / uA Level Power Test



IT6500 Series Wide-range
High-power DC Power Supply



IT6000C Bidirectional
Programmable DC Power Supply



Power Supply Test Solutions



IT7800 High Power
Programmable AC/DC Power Supply



IT6000D Series High Power
Programmable DC Power Supply



IT-M7700 High Performance
Programmable AC Power Supply



IT8700P Multi-channel
Programmable DC Electronic Load



IT8200 Series
AC / DC Electronic Load



Industrial Equipment Test Solutions



IT6000B Series
Regenerative Power System



IT-M3300 Series
Regenerative DC Electronic Load



IT8000 Series
Regenerative DC Electronic Load



IT7900P High Performance
Regenerative Grid Simulator



IT8900A/E High Performance
High Power DC Electronic Load



IT-M3140
Programmable DC Power Supply



Solar / Inverter Solutions



SAS1000
Solar Array Simulation Software



IT6000C Bidirectional
Programmable DC Power Supply



IT-N2100 Series
Solar Array Simulator



BSS2000
Battery Simulation Software



IT7900P Regenerative
Grid Simulator



IT8700P Multi-channel
Programmable DC Electronic Load



IoT Solutions



IT6400 Series Bipolar
DC Power Supply / Battery Simulator



IT6000C Bidirectional
Programmable DC Power Supply



IT-M3600
Regenerative Power System



IT8200 Series
AC / DC Electronic Load



IT-M3200 High Precision
Programmable DC Power Supply



IT8500G+ Series
Programmable DC Electronic Load



Research / Education Solutions



IT6300 Series
Triple Channels DC power supply



IT6900 Series
Wide-range Programmable
DC Power Supply



IT-M3100D Ultra-compact
Wide Range DC Power Supply



IT8800 Series
High Power DC Electronic Load



IT6800A/B Dual-range
Programmable DC Power Supply



IT8400 High Performance
High Power DC Electronic Load



Get the latest information——Visit ITECH's website online

Technical Support

Product registration

★ You can enjoy six-month extended warranty after registration within three months of purchase

The product overview provided in this catalog is for reference only; it is neither suggestions nor recommendation, and not a part of any contract. Due to the continual updating of our products, we reserve the right to change technical specifications and product specifications without notice. For more information, please feel free to visit www.itechate.com.